

Research Statement

Hierarchical and Adaptive Modelling for Protein–Drug Cofolding and Drug Design

Alireza Noroozi

anoroozi25@ku.edu.tr <https://alirzeanoroozi.github.io>

October 2026

Motivation

Predicting how a small molecule binds its protein target is one of the most important problems of computational drug discovery. Cofolding models—AlphaFold3, Boltz, Chai—have shown that a single network can jointly generate protein and ligand coordinates, and that doing so outperforms the older pipeline of predicting a structure first and docking into it afterwards. This is real progress, but it has arrived with a cost structure that now limits the field more than the modelling ideas themselves do.

The cost is one of resolution. These models represent every atom of the system at every layer: a 400-residue protein contributes on the order of three thousand heavy atoms, and attention over that set dominates both training and inference. The consequence is that we train on far less data than exists, with smaller models than we could otherwise afford, because the atomic representation is applied uniformly—to the hydrophobic core, to flexible surface loops, and to the binding site alike. Yet the information that determines binding is not uniformly distributed. A hydrogen bond geometry three Ångström from the ligand decides whether a pose is right; the side-chain rotamer of a solvent-exposed lysine forty Ångström away almost never does. We are paying full atomic price for a whole structure in order to get a handful of contacts correct.

My research programme starts from this observation: *resolution should follow information*. I propose to build cofolding models that reason at multiple levels of abstraction within a single system—coarse where the task is global geometry, atomic where the task is molecular recognition—and that learn where to spend detail rather than having it specified by hand.

Proposed approach

The programme decomposes into three stages, sketched in Figure 1, each of which raises its own research questions.

1. Global structure from a coarse model

The first stage learns the overall fold of the complex and the approximate position of the ligand using a reduced representation—C α traces for the protein, and a coarse-grained description of the ligand such as pharmacophore-like beads or fragment centroids. Reducing the token count by




Figure 1: Hierarchical cofolding. A coarse $C\alpha$ -level model establishes the global complex geometry and the approximate ligand placement; interface residues are then selected and refined with an all-atom model; the two are recombined into a consistent full-resolution complex.

roughly an order of magnitude makes it feasible to train on substantially more data, to use larger models under a fixed compute budget, and to run inference over large screening libraries.

The open question here is what *must* be retained. A pure $C\alpha$ trace discards side-chain identity, and with it much of what determines a pocket’s shape and chemistry. I plan to study intermediate representations— $C\alpha$ plus a learned per-residue embedding of side-chain identity and approximate orientation, or a small fixed number of pseudo-atoms per residue—and to characterise empirically how global placement accuracy degrades as representational detail is removed. The aim is a principled answer to how coarse one can go before the coarse stage stops being a useful initialisation for the fine one.

2. Adaptive selection of the interaction region

The second stage decides where atomic detail is warranted. The simplest criterion is geometric: select residues within a distance cutoff of the coarse ligand placement. This is a reasonable baseline but a brittle one, since it inherits any error in the coarse stage and cannot recover a pocket residue that the coarse model misplaced.

I am more interested in learned selection. The coarse model’s own attention over the ligand tokens is an obvious signal, and one that is available for free; a lightweight auxiliary head trained to predict per-residue contact probability is another. Both admit a soft, probabilistic treatment in which residues carry a continuous “refine me” weight rather than a binary label, and in which

the model can be calibrated to trade computational budget against the risk of excluding a residue that mattered. The failure mode to characterise carefully is the asymmetric one: including an unnecessary residue costs compute, while excluding a necessary one costs correctness. A selection policy that is well calibrated on this asymmetry is, I think, the technically most interesting part of the proposal.

3. All-atom refinement and consistent recombination

The third stage applies a full all-atom cofolding model to the selected region only, resolving side-chain conformations, hydrogen bonds, π - π stacking, halogen bonds and electrostatic complementarity at the resolution these interactions require. Because the region is small, this model can be larger and run for more sampling steps per atom than a whole-complex model of the same total cost.

Recombining the refined interface with the coarse global structure is not a matter of concatenation. The refined region must remain geometrically consistent with the scaffold that surrounds it, and the interface between the two resolutions is where artefacts will appear—bond-length and chain-continuity violations at the boundary, or a refined pocket that no longer fits the coarse fold. I plan to address this by making the boundary itself part of the learning problem: training the fine model conditioned on the coarse context so that it is never free to drift, and applying a short joint relaxation under a differentiable stereochemical objective. A useful test of whether this works is self-consistency—re-running the coarse model on the refined complex should reproduce the refined geometry.

Training, data and evaluation

The hierarchy has a data consequence that I find as interesting as the efficiency one. Different levels of abstraction can learn from different data. The coarse stage can be trained on the full PDB, on predicted structures, and on the large body of complexes where the global fold is reliable but atomic detail is not; the fine stage can be trained selectively on high-resolution crystal structures where the interface geometry is actually trustworthy. This lets the model use the large but noisy data where it is adequate, and the small but precise data where precision matters, instead of forcing one training distribution to serve both.

For evaluation I intend to go beyond aggregate RMSD. The relevant questions for this architecture are specific: at matched inference cost, does hierarchical cofolding achieve better pose accuracy than a uniform all-atom model? Where does it fail—and are its failures concentrated in the coarse stage’s global placement or in the selection policy? I plan to report accuracy explicitly as a function of compute, to stratify by pocket type and ligand flexibility, and to evaluate on temporally held-out and low-homology targets rather than only on random splits, since the generalisation claim is the one most easily overstated. Interaction-level metrics—whether specific hydrogen bonds are recovered—matter more here than global superposition, because they are what downstream affinity and design tasks depend on.

Longer-term direction

Adaptive resolution is a general principle, and protein–ligand cofolding is where I want to establish it rather than where I expect it to end. The same hierarchy applies to protein–protein interfaces, to nucleic acid complexes, and to systems too large for uniform atomic treatment. It also composes naturally with molecular dynamics, where coarse and fine representations have long coexisted but have rarely been learned jointly, and it offers a route to conformational ensembles: sampling cheaply at the coarse level and refining only the states that matter. Downstream, an efficient and accurate cofolding model is the natural front end for binding affinity prediction and for structure-based design, both of which are currently bottlenecked by the cost of generating reliable complex structures at scale.

Background

The three stages above map onto work I have already done, which is why I am confident the programme is executable rather than merely appealing.

Generative modelling over discrete biological sequences. In *AMP-DiT* (GenBio Workshop at ICML 2026) I built a conditional discrete diffusion transformer that generates antimicrobial peptides directly in sequence space, rather than inheriting representations from protein language models trained on full-length proteins. Conditioning on a single activity classifier generalised across several independent predictors, which indicated the model had learned antimicrobial structure rather than the idiosyncrasies of one scorer. In *IDPepDesign* I extended an insertion–deletion diffusion model to target-conditioned peptide binder design with a pooled target representation and residue-level cross-attention, improving perplexity from 17.1 to 11.3 and Fréchet protein distance from 1.84 to 0.75 while producing competitive interface quality across eleven benchmark targets. Both projects are exercises in exactly the question this proposal asks: what representation should a generative model operate over, and what is lost when it is changed.

Evaluation under conformational change. During my research internship with the DELTA team at Inria Nancy I worked on evaluating designed binders with molecular dynamics rather than single-structure confidence scores, contributing to *BinderEval* and to a new release of *COMPASS*. This is the part of the field that convinced me resolution and evaluation are the same problem viewed from two sides: a static score cannot see induced fit, and a model that cannot represent the interface at the right level of detail cannot be evaluated honestly at it either.

Design against real targets, with experimental feedback. In *AMP-BindGen* I designed peptide binders against the carbapenemases NDM-5 and KPC-3 in collaboration with clinical microbiologists at Koç University, ranking candidates by a composite of interface confidence, catalytic-site engagement, predicted activity and toxicity. Those designs went to the bench and results have come back. I have also worked on protein–ligand systems directly, designing protease-cleavable peptide linkers for antibody–drug conjugates in a covalently constrained Fv–linker–payload assembly, which is a cofolding problem in all but name.

Earlier foundations. My BSc thesis on sequence-only paratope prediction with protein language models was published in *Scientific Reports*, and prior work on federated learning for clinical data in *IEEE JBHI* taught me to be careful about evaluation protocols when data are scarce, heterogeneous and easy to overstate.

Fit

I am drawn to this problem because it sits where machine learning architecture meets structural biology: the central question—what level of detail does this part of the system actually require?—is simultaneously a modelling question and a biophysical one, and I do not think it can be answered well from either side alone. I would like to pursue it in a group working on structural or generative modelling of biomolecules, and I am equally happy for the emphasis to fall on the architectural and training side or on rigorous biophysical evaluation of what these models have and have not learned. What I would bring is experience building generative models over biological sequences from scratch, a habit of validating them against external predictors and wet-lab results rather than only against the objective they were trained on, and a working familiarity with molecular dynamics as a source of evidence rather than a post-hoc illustration.